

Cone crusher technical parameters

Model		Diameter of crushing cone (mm)	Max.feeding size (mm)	Width of discharge opening (mm)	Processing capacity (t/h)	Motor power (kw)	Swing frequency of main shaft	Total weight (t)	Dimensions (L×W×H) (mm)
PYB	600	600	65	12-25	40	30	356	5	2234×1370×1675
PYD			35	3-13	12-23			5.5	2234×1370×1675
PYB	900	900	115	15-50	50-90	55	333	11.2	2692×1640×2350
PYZ			60	5-20	20-65			11.2	2692×1640×2350
PYD			50	3-13	15-50			11.3	2692×1640×2350
PYB	1200	1200	145	20-50	110-168	110	300	24.7	2790×1878×2844
PYZ			100	8-25	42-135			25	2790×1878×2844
PYD			50	3-15	18-105			25.3	2790×1878×2844
PYB	1750	1750	215	25-50	280-480	160	245	50.3	3910×2894×3809
PYZ			185	10-30	115-320			50.3	3910×2894×3809
PYD			85	5-13	75-230			50.2	3910×2894×3809
PYB	2200	2200	300	30-60	59-1000	280-260	220	80	4622×3302×4470
PYZ			230	10-30	200-580			80	4622×3302×4470
PYD			100	5-15	120-340			81.4	4622×3302×4470