

## High efficiency concentrator machine technical parameters

Specification		Concentration pond		Deposit square (m <sup>2</sup> )	Harrow part			Motor		Processing capacity (t/d)	Total weight (kg)
Model	Specification	Inner diameter	Depth (mm)	Pond degree	Method	Height (m)	Rotation time (min/r)	Driving	Lifting		
NZS-1	Φ1.8m	1.8	1.8	2.54	Manual	0.16	2	Y90L-6 1.1KW	----	5.6	1.8
NZS-3	Φ3.6m	3.6	1.8	10.2	Manual	0.35	2.5	Y90L-6 1.1KW	----	22.4	4.1
NZS-6	Φ6m	6	3	28.3	Manual	0.2	3.7	Y90S-4 1.1KW	----	62	10.2
NZSF-6	Φ6m	6	3	28.3	Manual	----	3.7	Y90S-4 1.1KW	----	62	4.8
NZ-9	Φ9m	9	3	63.6	Auto	0.25	4.34	Y132S-6 3KW	XWD0.8 -3 0.8KW	140	8.1
NZS-9	Φ9m	9	3	63.6	Manual	0.25	4.34	Y132S-6 3KW	----	140	7.1
NZS-12	Φ12m	12	3.5	113	Manual	0.25	5.28	Y132S-6 3KW	----	250	10.5
NZ-15	Φ15m	15	4.4	176	Auto	0.4	10.4	JTC752A- 44 5.2KW	Y112M- 6 2.2KW	350	24.7
NZ-20	Φ20m	20	4.4	314	Auto	0.4	10.4	JTC752A- 44 5.2KW	Y112M- 6 2.2KW	960	27.5
NZ-30	Φ30m	30	7.165	707	----	0.61	13.7	Y100L1-4 2.2×2KW	YCJ132- S 1.5KW	----	34.8
NZS-45	Φ45m	45	4.636	1590	Manual	----	20	JTC672A- 44 5.2KW	YCJ160- S 2.2KW	515	51.8
NT-15	Φ15m	15	3.5	177	----	----	8.4	Y132M2-6 5.5KW	----	390	12



China Largest Mining Machinery  
Manufacturer

Tel: +86-371-67833161/67833171

MSN Online: [hxjq@hxjq.cn](mailto:hxjq@hxjq.cn)

E-mail: [sales@hxjq.com](mailto:sales@hxjq.com) [sinohxjq@hxjq.com](mailto:sinohxjq@hxjq.com)

Yahoo: [hongxingmachinery@yahoo.com](mailto:hongxingmachinery@yahoo.com)

NQ-18	Φ18m	18	3.5	255	----	----	10	Y132M2-6 5.5KW	----	560	11
NQ-24	Φ24m	24	3.4	452	----	----	12.7	Y160M-6 7.5KW	----	1000	25.3
NG-30	Φ30m	30	3.6	707		----	16	Y160M-6 7.5KW	----	1570	29.4
NJ-38	Φ38m	38	4.9	1134	----	----	10-25	JZT252-4 11KW	Y160M- 6 7.5KW	1600	60.2
NT-45	Φ45m	45	5.05	1590	Auto	----	19.3	Y160L-6 11KW	----	2400	63.6
NTJ-53	Φ53m	53	5.07	2202	----	----	23.18	Y180L-6 15kw	----	6250	84.8
NT-100	Φ100m	100	5.65	7846	----	----	43	Y180L-6 15KW	----	3030	204.6